Application

Light building element with symmetric light distribution. Light building elements are luminous design features for public areas. They are ideally suited for delineating and structuring interior and exterior spaces such as landscape areas, plazas, building entrances and atria.

Materials

Clear safety glass
A380 aluminum alloy
High-strength A572 stainless steel alloy
Integral surge protector
Galvanized steel anchorage
Pure anodized aluminum reflector

NRTL listed to North American Standards, suitable for wet locations

Protection class IP 65

Weight: 59.5 lbs.

Electrical

Operating voltage 120-277V AC
Minimum start temperature -20° C
Maximum ambient temperature 50° C
LED module wattage 19.5 W
System wattage 24.0 W
Controllability 0-10V dimmable

Color rendering index Ra > 80

Luminaire lumens 1500 lm

LED color temperature

4000K (K4) 3500K (K35) 3000K (K3) 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors

 Black (BLK)
 Bronze (BRZ)

 Silver (SLV)
 White (WHT)

 RAL:
 CUS:



Building element · Symmetric					
	LED	А	В	С	
B84754	19.5 W	61/4	997/8	1373/4	

Type:

BEGA Product:

Project: Modified:

Available options

B71207 Direct burial anchorage (replaces included

anchorage kit, pre-shippable)

CUS Custom finish

DALI-2 Digital addressable lighting interface

FSC Fusing

MGU Marine grade undercoat

RAL RAL finish

Included (available for pre-shipment)

B79827 Anchorage kit

