

Application

Designed for the general illumination of trees, walls, signage and other surfaces where conventional in-grades or floodlights do not meet the requirements.

Materials

- Clear safety glass
- Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy
- High temperature silicone gasket
- Fully potted waterstopper cable
- Mechanically captive stainless steel fasteners
- Pure anodized aluminum reflector surface

NRTL listed to North American Standards, suitable for wet locations
 Protection class IP 67

Weight: 5.7 lbs.

Electrical

Operating voltage	120-277VAC
Minimum start temperature	-30° C
LED module wattage	20.2 W
System wattage	26.0 W
Controllability	0-10V dimmable
Color rendering index	Ra > 80
Luminaire lumens	2824 lm
LED service life (L70)	60000 hrs

LED color temperature

- 4000K (K4)
- 3500K (K35)
- 3000K (K3)
- 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors

Black (BLK)	Bronze (BRZ)
Silver (SLV)	White (WHT)
RAL:	CUS:

Type:


BEGA Product:

Project:

Modified:

Available options

B71246	Direct burial anchorage (replaces included anchorage kit, pre-shippable)
CUS	Custom finish
DALI-2	Enabled for DALI control system
FSC	Fusing
NTB	Natural bronze (premium finish)
RAL	RAL Classic, matte finish



On-ground luminaire · Symmetric

	LED	β	A	B
B84757	20.2 W	28°	8	5 1/2

