

**Application**

Designed for the general illumination of trees, walls, signage and other surfaces where conventional in-grades or floodlights do not meet the requirements.

**Materials**

Clear safety glass  
 Marine grade, copper free ( $\leq 0.3\%$  copper content) A360.0 aluminum alloy  
 Mechanically captive stainless steel fasteners  
 Fully potted waterstopper cable  
 High temperature silicone gasket  
 Pure anodized aluminum reflector surface

**NRTL** listed to North American Standards, suitable for wet locations  
 Protection class IP 67

**Weight:** 5.8 lbs.

**Electrical**

Operating voltage	120-277VAC
Minimum start temperature	-20° C
LED module wattage	24.1 W
System wattage	29.0 W
Controllability	0-10V dimming down to 1%
Color rendering index	Ra > 90
Luminaire lumens	596 lm
LED service life (L70)	60000 hrs

**LED color temperature**

4000K (K4)  
 3500K (K35)  
 3000K (K3)  
 2700K (K27)


**BEGA** can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

**Finish**

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

**Available colors**

Black (BLK)	Bronze (BRZ)
Silver (SLV)	White (WHT)
Natural Bronze (NTB)	RAL:
CUS:	



**On-ground luminaire · Asymmetric**

	LED	$\beta$	A	B
<b>B84758</b>	24.1 W	11.5°	8	7 1/2

Type:

BEGA Product:

Project:

Modified:

**Available options**

B71246	Direct burial anchorage (replaces included anchorage kit, pre-shippable)
CUS	Custom finish
DALI-2	Enabled for DALI control system
FSC	Fusing
NTB	Natural bronze (premium finish)
RAL	RAL Classic, matte finish

