

Application
BEGA system bollard tube with photocell and passive infrared motion sensor. An accompanying DALI-2 enabled bollard head must be selected for proper installation. Default operating sequence: Automatic ON to 30% output when ambient levels <500lux. Increase to 100% output for 10mins upon motion detection, then return to 30% output resting state. Automatic OFF when ambient levels >500lux. Consult factory for custom motion sensor settings.

Materials
Extruded aluminum
Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy
Integral DALI-2 PIR motion and light sensor
Interlocking stainless steel mounting mechanism for attachment of head and tube
Pre-wired with 5-pole plug-in connectors for ease of installation
Stainless steel helicoils
Stainless steel hardware
Anchor bolts provided with (2) hex nuts and (2) flat washers
Threaded stainless steel anchor rods

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 65

Weight: 12.4 lbs.

Electrical	
Operating voltage	120-277VAC
Minimum start temperature	-20° C
Controllability	DALI-2

Finish
All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors	
Black (BLK)	Bronze (BRZ)
Natural Bronze (NTB)	Silver (SLV)
White (WHT)	RAL:
CUS:	

Type:
BEGA Product:
Project:
Modified:

Available options	
70895	Direct burial anchorage (replaces included anchorage kit, pre-shippable)
CUS	Custom finish
MGU	Marine grade undercoat
NTB	Natural bronze (premium finish)
RAL	RAL Classic, matte finish

Included (available for pre-shipment)
B79817 Anchorage kit



System bollard tube · Integral DALI-2 enabled photocell and PIR motion sensor

	A	B
B84762	6 1/4	32



The overview provides a compact summary of the possibilities for combining the various bollard heads with the bollard tubes and their additional functions.

For each bollard head you can find matching bollard tubes with and without components.

System bollard heads with compatible tubes							
BEGA bollard tubes □ in inches		□ 6 1/4	□ 8 5/8	□ 6 1/4	□ 8 5/8	□ 6 1/4	□ 8 5/8
	Without components in two heights	•	•	•	•	•	•
	With integral PIR motion sensor	•	•	•	•	•	•
	With drive-through protection		•		•		•
	With integral GFCI outlet		•		•		•
	Wood bollard tubes	•	•	•	•	•	•

Compatible heads · □ 6 1/4

System bollard head · Unshielded with safety guard · 360°			
	LED	A	B
B84680	7.9 W	6 1/4	7

System bollard head · Shielded · 360°			
	LED	A	B
B84690	16.8 W	6 1/4	5

System bollard head · Non-illuminated cap			
		A	B
B71124		6 1/4	0 3/4