

Application
BEGA system bollard tube with photocell and passive infrared motion sensor. An accompanying DALI-2 enabled bollard head must be selected for proper installation. Default operating sequence: Automatic ON to 30% output when ambient levels <500lux. Increase to 100% output for 10mins upon motion detection, then return to 30% output resting state. Automatic OFF when ambient levels >500lux. Consult factory for custom motion sensor settings.

Materials
Extruded aluminum
Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy
Integral DALI-2 PIR motion and light sensor
Pre-wired with 5-pole plug-in connectors for ease of installation
Interlocking stainless steel mounting mechanism for attachment of head and tube
Stainless steel helicoils
Stainless steel hardware
Anchor bolts provided with (2) hex nuts and (2) flat washers
Threaded stainless steel anchor rods

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 65

Weight: 26.9lbs.

Electrical
Operating voltage 120-277VAC
Minimum start temperature -20° C
Controllability DALI-2

Finish
All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors
Black (BLK) Bronze (BRZ)
Natural Bronze (NTB) Silver (SLV)
White (WHT) RAL:
CUS:

Type:
BEGA Product:
Project:
Modified:

Available options
70896 Direct burial anchorage (replaces included anchorage kit, pre-shippable)
CUS Custom finish
MGU Marine grade undercoat
NTB Natural bronze (premium finish)
RAL RAL Classic, matte finish

Included (available for pre-shipment)
B79818 Anchorage kit



System bollard tube · Integral DALI-2 enabled photocell and PIR motion sensor

B84763	A	B
	8 ⁵ / ₈	34 ¹ / ₄



The overview provides a compact summary of the possibilities for combining the various bollard heads with the bollard tubes and their additional functions.

For each bollard head you can find matching bollard tubes with and without components.

System bollard heads with compatible tubes							
BEGA bollard tubes □ in inches		□ 6 1/2	□ 8 5/8	□ 6 1/2	□ 8 5/8	□ 6 1/2	□ 8 5/8
	Without components in two heights	•	•	•	•	•	•
	With integral PIR motion sensor	•	•	•	•	•	•
	With drive-through protection		•		•		•
	With integral GFCI outlet		•		•		•
	Wood bollard tubes	•	•	•	•	•	•

Compatible heads · 8 5/8

System bollard head · Unshielded with safety guard · 360°

	LED	A	B
B84681	15.7 W	8 5/8	9 1/4

System bollard head · Shielded · 360°

	LED	A	B
B84691	25.2 W	8 5/8	7 1/2

System bollard head · Non-illuminated cap

	A	B
B71125	8 5/8	0 3/4