

Application

An in-grade luminaire for installation in concrete or soil, and intended to provide a uniform wall wash. Designed to bear pressure loads up to 4,400 lbs. from vehicles with pneumatic tires. The luminaire must not be used for traffic lanes where it is subject to horizontal pressure from vehicles braking, accelerating or changing direction.

Materials

- Clear safety glass
- 316 grade stainless steel
- Fully potted waterstopper cable
- High temperature silicone gasket
- Composite installation housing
- Pure anodized aluminum reflector surface

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 68

Weight: 3.3 lbs.

Electrical

Operating voltage	120-277VAC
Minimum start temperature	-30° C
LED module wattage	4.0W
System wattage	7.0W
Controllability	0-10V dimmable
Color rendering index	Ra > 80
Luminaire lumens	440lm
LED service life (L70)	60000hrs

LED color temperature

- 4000K (K4)
- 3500K (K35)
- 3000K (K3)
- 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

#4 brushed stainless steel. Custom colors are not available.

Type:

BEGA Product:

Project:


Modified:

Available options

DALI-2	Enabled for DALI control system
FSC	Fusing
NSL	Non-skid lens

Included (available for pre-shipment)

B70693	Installation housing
--------	----------------------



In-grade luminaire · Wall washer

	LED	β	A	B	C
B84767	4.0W	52°	5 ³ / ₄	10 ⁵ / ₈	6 ³ / ₄

