

Application

Building elements are luminous design features for public spaces. They are ideally suited for delineating and structuring spaces such as plazas, building entrances, and atria. Simply order the building element head plus a required building element pole in wood or metal with optional integral components. Both modules can be joined together easily and quickly during installation.

Materials

- Clear UV-stabilized acrylic diffuser
- Marine grade, copper free (≤ 0.3% copper content) A360.0 aluminum alloy
- High temperature silicone gasket
- Stainless steel hardware
- Pure anodized aluminum reflector

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 65

Weight: 9.3 lbs.

Electrical

- Operating voltage120-277V AC
- Minimum start temperature-30° C
- LED module wattage19.5 W
- System wattage24.0 W
- Controllability0-10V dimmable
- Color rendering indexRa > 80
- Luminaire lumens2442 lm
- LED service life (L70)60000 hrs

LED color temperature

- 4000K (K4)
- 3500K (K35)
- 3000K (K3)
- 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors

- Black (BLK)
- Silver (SLV)
- RAL:
- Bronze (BRZ)
- White (WHT)
- CUS:

Type:

BEGA Product:

Project:

Modified:

Available options

- CUSCustom finish
- DALI-2Digital addressable lighting interface
- ELV/TRIACElectronic low voltage/TRIAC dimming
- FSCFusing
- MGUMarine grade undercoat
- RALRAL finish



System building element head · Symmetric			
	LED	A	B
B84814	19.5 W	5 1/4	19 9/8



System building elements summary

BEGA

This overview provides a compact summary of the possibilities for combining the various building element heads with poles and their additional functions.

For each building element head you can find matching poles with and without components.

System building elements with compatible poles		Symmetric			Asymmetric			Unshielded			Unshielded			Symmetric			Asymmetric		
Ø in inches		ø5 1/4	ø6 3/4	ø8 3/8	ø5 1/4	ø6 3/4	ø8 3/8	ø5 1/4	ø6 3/4	ø8 3/8	ø5 1/4	ø6 3/4	ø8 3/8	ø5 1/4	ø6 3/4	ø8 3/8	ø5 1/4	ø6 3/4	ø8 3/8
	Base plate • without components	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
	Direct burial • without components	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
	Base plate • wood	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
	Direct burial • wood	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
	Base plate • 1 adjustable floodlight		•	•		•	•		•	•									
	Direct burial • 1 adjustable floodlight		•	•		•	•		•	•									
	Base plate • 2 adjustable floodlights		•	•		•	•		•	•									
	Direct burial • 2 adjustable floodlights		•	•		•	•		•	•									

Compatible poles • Ø5 1/4

System building element pole • Base plate			
	A	B	C
B84709	5 1/4	138 1/4	13 3/8

System building element pole • Direct burial			
	A	B	C
B84708	5 1/4	138 1/8	31 1/2

Wood system building element pole • Base plate			
	A	B	C
B84711	5 1/4	138 1/2	13 3/8

Wood system building element pole • Direct burial			
	A	B	C
B84710	5 1/4	138 5/8	31 1/2