

Application

On-ground luminaire for illuminating horizontal surfaces from very low mounting heights such as squares, entrances and wide pathways. Provided with mounting system that allows the luminaire to be adjusted independent of anchor bolt orientation.

Materials

- Clear safety glass with optical texture
- Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy
- High temperature silicone gasket
- Mechanically captive stainless steel fasteners
- Galvanized steel anchorage
- Pure anodized aluminum reflector

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 67

Weight: 5.8 lbs.

Electrical

- Operating voltage120-277V AC
- Minimum start temperature-30° C
- LED module wattage16.4 W
- Controllability0-10V dimmable
- Color rendering indexRa > 80
- Luminaire lumens712 lm
- LED service life (L70)60000 hrs

LED color temperature

- 4000K (K4)
- 3500K (K35)
- 3000K (K3)
- 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors

- Black (BLK)

Silver (SLV)

Natural Bronze (NTB)

CUS:
- Bronze (BRZ)

White (WHT)

RAL:

Type:

BEGA Product:

Project:

Modified:

Available options

- CUS

FSC

MGU

NTB


RAL
- Custom finish

Fusing

Marine grade undercoat

Natural bronze (premium finish)

RAL finish



On-ground surface washer · Asymmetric				
	LED	A	B	C
B84815	16.4 W	9	6 ³ / ₄	7 ¹ / ₈

