

Application

Light building elements are luminous design features for public areas. They are ideally suited for delineating and structuring interior and exterior spaces such as landscape areas, plazas, building entrances and atriums.

Materials

- White UV-stabilized acrylic diffuser
- Die-cast aluminum
- Extruded aluminum pole shaft
- Marine grade, copper free ($\leq 0.3\%$ copper content) A360.0 aluminum alloy
- High temperature silicone gasket
- Anchorage must be buried
- Galvanized steel anchorage
- Mounting hardware included
- Mounting template included

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 65

Weight: 30.0 lbs.

Electrical

Operating voltage	120-277V AC
Minimum start temperature	-30° C
LED module wattage	15.2 W
System wattage	20.0 W
Controllability	0-10V, TRIAC, and ELV dimmable
Color rendering index	Ra > 80
Luminaire lumens	2468 lm
LED service life (L70)	60000 hrs

LED color temperature

- 4000K (K4)
- 3500K (K35)
- 3000K (K3)
- 2700K (K27)


BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors

Black (BLK)	Bronze (BRZ)
Silver (SLV)	White (WHT)
RAL:	CUS:



Building element · Unshielded

	LED	A	B	C
B84894	15.2 W	5 ⁵ / ₈	18 ¹ / ₂	97 ³ / ₈

BEGA 1000 BEGA Way, Carpinteria, CA 93013 (805) 684-0533 info@bega-us.com

Due to the dynamic nature of lighting products and the associated technologies, luminaire data on this sheet is subject to change at the discretion of BEGA North America. For the most current technical data, please refer to bega-us.com
© copyright BEGA 2026 Updated 03/12/26

Type:

BEGA Product:

Project:

Modified:

Available options

B71242	Direct burial
CUS	Custom finish
DALI-2	Enabled for DALI control system
FSC	Fusing
MGU	Marine grade undercoat
RAL	RAL Classic, matte finish

Included (available for pre-shipment)

B71243	Anchorage Kit
--------	---------------

