

Application

Pole-top luminaires with asymmetrical light distribution. The asymmetrical light distribution is ideal for illuminating parking areas, roadways and walkways. DarkSky Approved (2700K and 3000K only).

Materials

Optically textured UV-stabilized acrylic diffuser
 Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy
 High temperature silicone gasket
 Mounting hardware included
 Pure anodized aluminum reflector

NRTL listed to North American Standards, suitable for wet locations
 Protection class IP 65

Weight: 10.1 lbs.

Electrical

LED module wattage	37.0W
System wattage	44.0W
Color rendering index	Ra > 80
Luminaire lumens	3622 lm
LED service life (L70)	60000 hrs

LED color temperature

4000K (K4)
 3500K (K35)
 3000K (K3) (DarkSky Approved)
 2700K (K27) (DarkSky Approved)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish


All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors

Black (BLK)	Bronze (BRZ)
Silver (SLV)	White (WHT)
RAL:	CUS:

Available options

CUS	Custom finish
DALI-2	Enabled for DALI control system
FSC	Fusing
MGU	Marine grade undercoat
RAL	RAL Classic, matte finish



Pole-top luminaire · Asymmetric

	LED	A	B
B85197	37.0W	13	14 ^{7/8}

