

Application

Pole-top luminaires with asymmetrical light distribution. The asymmetrical light distribution is ideal for illuminating parking areas, roadways and walkways. Luminaire includes DALI standard with Zhaga interface and optional BEGA Connect capability. DarkSky Approved (2700K and 3000K only).

Materials

Optically textured UV-stabilized acrylic diffuser
 Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy
 High temperature silicone gasket
 Mounting hardware included
 Pure anodized aluminum reflector

NRTL listed to North American Standards, suitable for wet locations
 Protection class IP 65

Weight: 10.1 lbs.

Electrical

Operating voltage 120-277V AC
 Minimum start temperature -40° C
 LED module wattage 37.0W
 System wattage 44.0W
 Controllability DALI D4i
 Color rendering index Ra > 80
 Luminaire lumens 3622lm
 LED service life (L70) 60000hrs

LED color temperature

4000K (K4)
 3500K (K35)
 3000K (K3) (DarkSky Approved)
 2700K (K27) (DarkSky Approved)


BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors

Black (BLK) Bronze (BRZ)
 Silver (SLV) White (WHT)
 RAL: CUS:



Pole-top luminaire · Asymmetric with Zhaga Receptacle

	LED	A	B
B85198	37.0W	13	15 ^{3/8}

Type:

BEGA Product:

Project:

Modified:

Available options

CUS Custom finish
 FSC Fusing
 MGU Marine grade undercoat
 RAL RAL Classic, matte finish

Available accessories

B71210 Air Connector · Zhaga Book 18 Ed 3.0

See individual accessory spec sheet for details.

