Application

Bollard with 360° light distribution in stainless steel. This luminaire is designed to illuminate paths, entrances and driveways in private and public areas

Materials

Chemically hardended soda-lime glass Corrosion-resistant 304 grade stainless steel Zinc plated carbon steel anchor bolts with template Pure anodized aluminum reflector

 $\ensuremath{\mathsf{NRTL}}$ listed to North American Standards, suitable for wet locations Protection class IP 65

Weight: 38.6lbs.

Electrical

Operating voltage 120-277V AC Minimum start temperature -30° C LED module wattage 16.5 W System wattage 19.0 W Controllability 0-10V dimma

Controllability 0-10V dimmable
Color rendering index Ra > 80
Luminaire lumens 1481 lm

Luminaire lumens
LED service life (L70)

Ra > 80

1481 lm

60000 hrs

LED color temperature

4000K (K4) 3500K (K35) 3000K (K3) 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

#4 brushed stainless steel. Custom colors are not available.

Type:

BEGA Product:

Project: Modified:

Included (available for pre-shipment)

B79818 Anchorage kit





Bollard ⋅ Shielded with reflector ⋅ 360°				
	LED	Α	В	С
B88061	16.5 W	81/8	437/8	11 ⁷ / ₈