

Application
An edge-lit luminaire designed with exquisite visual interest for the illumination of walkways and open pedestrian landscape areas.

Materials
Optically textured UV-stabilized acrylic diffuser
Die-cast aluminum
Extruded aluminum pole shaft
High temperature silicone gasket
Stainless steel hardware
Integral surge protector
Pure anodized aluminum reflector

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 65

Weight: 62.6lbs.

EPA (Effective projection area): 64.6 sq. ft.

Electrical
Operating voltage 120-277VAC
Minimum start temperature -30° C
LED module wattage 32.0W
System wattage 38.0W
Controllability 0-10V dimming down to 1%
Color rendering index Ra > 80
Luminaire lumens 2611 lm
LED service life (L70) 60000hrs

LED color temperature
4000K (K4)
3500K (K35)
3000K (K3)
2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish
All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors

Black (BLK)	Bronze (BRZ)
Silver (SLV)	White (WHT)
RAL:	CUS:

Type:
BEGA Product:
Project:
Modified:

Available options

CUS	Custom finish
MGU	Marine grade undercoat
RAL	RAL Classic, matte finish



Light building element · Symmetric					
	LED	A	B	C	D
B88165	32.0W	20 ¹ / ₈	21 ⁵ / ₈	153 ⁷ / ₈	31 ¹ / ₂