

Application

Pole-top luminaire with symmetric light distribution and shallow height. The symmetric light distribution is ideal for illuminating squares, plazas and other open areas.

Materials

White high-density polyethylene diffuser  
Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy

NRTL listed to North American Standards, suitable for wet locations  
Protection class IP 65

Weight: 25.5 lbs.

EPA (Effective projection area): 1.0 sq. ft.

Electrical

Operating voltage 120, 220-240 OR 277 VAC  
Minimum start temperature -30° C  
LED module wattage 16.0W  
System wattage 19.0W  
Controllability 0-10V dimmable  
Color rendering index Ra > 80  
Luminaire lumens 1809lm  
LED service life (L70) 60000hrs

LED color temperature

4000K (K4)  
3500K (K35)  
3000K (K3)  
2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors

Black (BLK) Bronze (BRZ)  
Silver (SLV) White (WHT)  
RAL: CUS:

Type:

BEGA Product:

Project:

Modified:

Available options

CUS Custom finish  
FSC Fusing  
MGU Marine grade undercoat  
RAL RAL finish



Pole-top luminaire · Symmetric			
	LED	A	B
B88260	16.0W	27 1/2	12 5/8