

Application

A ground mounted luminaire with low mounting height and 180° light distribution. The narrow beam light distribution is ideally suited for illuminating and grazing ground surfaces. Provided with mounting system that allows the luminaire to be adjusted independent of anchor bolt orientation.

Materials

Chemically hardened soda-lime glass
A380 aluminum alloy
High temperature silicone gasket
Glass collimator

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 67

Weight: 6.0 lbs.

Electrical

Operating voltage	120-277VAC
Minimum start temperature	-30° C
LED module wattage	9.0W
System wattage	12.0W
Controllability	0-10V dimmable
Color rendering index	Ra > 80
Luminaire lumens	145lm
LED service life (L70)	60000hrs

LED color temperature

4000K (K4)
3500K (K35)
3000K (K3)
2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors

Black (BLK)	Bronze (BRZ)
Silver (SLV)	White (WHT)
Natural Bronze (NTB)	RAL:
CUS:	

Type:

BEGA Product:

Project:


Modified:

Available options

CUS	Custom finish
FSC	Fusing
MGU	Marine grade undercoat
RAL	RAL finish

Included (available for pre-shipment)

B79815	Anchorage kit
--------	---------------



On-ground luminaire · 180° light output

	LED	A	B
B88360	9.0W	6 ³ / ₄	7 ¹ / ₂

