


BEGA

Photometric Filename: 88978.ies

TEST: BE_88977
TEST LAB: BEGA
DATE: 3/1/2017
LUMINAIRE: 88 978
LAMP: (2) 19.2W LED

*Report based on a single IES file, see below for twin head iso-footcandle template




Characteristics

IES Classification	Type II
Longitudinal Classification	Very Short
Lumens Per Lamp	N.A. (absolute)
Total Lamp Lumens	N.A. (absolute)
Luminaire Lumens	2352
Downward Total Efficiency	N.A.
Total Luminaire Efficiency	N.A.
Luminaire Efficacy Rating (LER)	102
Total Luminaire Watts	23
Ballast Factor	1.00
Upward Waste Light Ratio	0.00
Max. Cd.	898.3 (275H, 32.5V)
Max. Cd. (<90 Vert.)	898.3 (275H, 32.5V)
Max. Cd. (At 90 Deg. Vert.)	0 (0.0%Lum)
Max. Cd. (80 to <90 Deg. Vert.)	100.4 (4.3%Lum)
Cutoff Classification (deprecated)	N.A. (absolute)


Lum. Classification System (LCS)

LCS Zone	Lumens	%Lamp	%Lum
FL (0-30)	240.5	N.A.	10.2
FM (30-60)	698.7	N.A.	29.7
FH (60-80)	261.8	N.A.	11.1
FVH (80-90)	15.4	N.A.	0.7
BL (0-30)	236.6	N.A.	10.1
BM (30-60)	669.5	N.A.	28.5
BH (60-80)	221.5	N.A.	9.4
BVH (80-90)	8.1	N.A.	0.3
UL (90-100)	0.0	N.A.	0.0
UH (100-180)	0.0	N.A.	0.0
Total	2352.1	N.A.	100.0

BUG Rating B1-U0-G1



Grid Spacing = 15 ft.



In the interest of product improvement, BEGA reserves the right to make technical changes without notice.

BEGA 1000 Bega Way, Carpinteria, CA 93013 (805)684-0533 Fax (805)566-9474 www.bega-us.com © Copyright BEGA-US 2018

7/10/2018