Application

A large-scale, high-output floodlight with mounting yoke designed to illuminate bridges, monuments, building facades or large signage. For use in ambient temperatures that do not exceed 45° C.

Materials

Clear safety glass

Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy

High temperature silicone gasket Stainless steel mounting yoke

Composite concentric ring louver

Pure anodized aluminum reflector surface

BEGA Hybrid Optics®

Silicone optic with excellent high temperature and UV stability

NRTL listed to North American Standards, suitable for wet locations

Protection class IP 67

Weight: 48.5 lbs.

Electrical

Operating voltage 120-277VAC Minimum start temperature -30° C Maximum ambient temperature 45°C LED module wattage 250.2W System wattage 285.0W Controllability 0-10V dimmable

Color rendering index Ra > 80Luminaire lumens 8597 lm

LED service life (L70) 60000 hrs

LED color temperature

4000K (K4) 3500K (K35) 3000K (K3) 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors

Black (BLK) Bronze (BRZ) Silver (SLV) White (WHT) Natural Bronze (NTB) RAL:

CUS:

Type:

BEGA Product:

Project: Modified:

Available options

B71101 Glare shield · 180° Custom finish **CUS**

Fusing **FSC**

MGU Marine grade undercoat NTB Natural bronze (premium finish)

RAL RAL finish


VRY Vibration resisting yoke

Available accessories

B70761 Cross beam · 3 floodlights Pole cap · 2 floodlights Pole cap · 3 floodlights B70762 B70763 B70764 Pole cap · 4 floodlights B70765 Cross beam · 6 floodlights B79550 Pole mount arm B79551 Wall mount arm B79555 Pole-top mounting hub

See individual accessory spec sheet for details.





High-performance floodlight · Very narrow beam

	LED		А	В	С	
B98018	250.2 W	4.7°	191/.	203/.	121/2	