

Application

Pole-top luminaire with adjustable, indirect light distribution. A symmetric distribution is produced when the top reflector is set in the horizontal position and becomes asymmetric when the reflector is adjusted from 0° to 30°.

Materials

- Clear safety glass
- Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy
- High temperature silicone gasket
- Pure anodized aluminum reflector surface

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 65

Weight: 33.0 lbs.

EPA (Effective projection area): 3.2 sq. ft.

Electrical

- | | |
|---------------------------|--------------------------------|
| Operating voltage | 120V or 277V AC |
| Minimum start temperature | -10° C |
| LED module wattage | 35.7 W |
| System wattage | 39.7 W |
| Controllability | 0-10V, TRIAC, and ELV dimmable |
| Color rendering index | Ra > 90 |
| Luminaire lumens | 2776 lm |
| LED service life (L70) | 60000 hrs |

LED color temperature

- 4000K (K4)
- 3500K (K35)
- 3000K (K3)
- 2700K (K27)


BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors

- | | |
|--------------|--------------|
| Black (BLK) | Bronze (BRZ) |
| Silver (SLV) | White (WHT) |
| RAL: | CUS: |



Type:

BEGA Product:

Project:

Modified:

Available options

- | | |
|-----|------------------------|
| MGU | Marine grade undercoat |
|-----|------------------------|



Indirect pole-top luminaire · Adjustable · Cut-off optics			
	LED	A	B
B98019	35.7 W	31 1/2	21 1/4