

Application

A bollard with shielded asymmetric light distribution. Designed for effective lighting of landscapes, pathways, and open spaces from low mounting heights. The fully shielded design provides visual comfort while illuminating ground surfaces. Provided with mounting system that allows the luminaire to be adjusted independent of anchor bolt orientation. DarkSky Approved (2700K and 3000K only)

Materials

Clear safety glass
Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy
Mechanically captive stainless steel fasteners
Silicone applied robotically to casting, plasma treated for increased adhesion
Galvanized steel anchorage
Pure anodized aluminum reflector

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 65

Weight: 10.8lbs.

Electrical

Operating voltage 120, 240 or 277VAC
Minimum start temperature -30° C
LED module wattage 11.6W
System wattage 14.0W
Controllability 0-10V dimmable
Color rendering index Ra > 80
Luminaire lumens 1361 lm
LED service life (L70) 60000hrs

LED color temperature

4000K (K4)
3500K (K35)
3000K (K3) (DarkSky Approved)
2700K (K27) (DarkSky Approved)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors

Black (BLK) Bronze (BRZ)
Silver (SLV) White (WHT)
Natural Bronze (NTB) RAL:
CUS:

Type:

BEGA Product:

Project:

Modified:


Available options

70895 Direct burial anchorage (replaces included anchorage kit, pre-shippable)
AMB Amber LED
CUS Custom finish
FSC Fusing
MGU Marine grade undercoat
NTB Natural bronze (premium finish)
RAL RAL finish

Included (available for pre-shipment)

B79817 Anchorage kit

• A •



Bollard · Wide spread			
	LED	A	B
B99056	11.6W	7 1/2	21 5/8

