

Application

Unshielded light is ideally suited for the illumination of pathways, entrance areas, or in a garden or residential area. Provided with mounting system that allows the luminaire to be adjusted independent of anchor bolt orientation.

Materials

Clear safety glass with white ceramic coating  
Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy  
Silicone applied robotically to casting, plasma treated for increased adhesion  
Mechanically captive stainless steel fasteners

NRTL listed to North American Standards, suitable for wet locations  
Protection class IP 65

Weight: 17.6lbs.

Electrical

Operating voltage120-277VAC  
Minimum start temperature-20° C  
LED module wattage22.8W  
System wattage32.0W  
Controllability0-10V dimming down to 0.1%  
Color rendering indexRa > 80  
Luminaire lumens1432lm  
LED service life (L70)60000hrs

LED color temperature

4000K (K4)  
3500K (K35)  
3000K (K3)  
2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors

Black (BLK)Bronze (BRZ)  
Silver (SLV)White (WHT)  
Natural Bronze (NTB)RAL:  
CUS:

Type:

BEGA Product:

Project:


Modified:

Available options

70895Direct burial anchorage (replaces included anchorage kit, pre-shippable)  
CUSCustom finish  
FSCFusing  
MGUMarine grade undercoat  
NTBNatural bronze (premium finish)  
RALRAL finish

Included (available for pre-shipment)

B79817Anchorage kit



| Bollard · Light emission on two sides |       |                               |                                |                               |                               |
|---------------------------------------|-------|-------------------------------|--------------------------------|-------------------------------|-------------------------------|
|                                       | LED   | A                             | B                              | C                             | D                             |
| B99330                                | 22.8W | 4 <sup>3</sup> / <sub>4</sub> | 39 <sup>3</sup> / <sub>8</sub> | 3 <sup>1</sup> / <sub>8</sub> | 6 <sup>3</sup> / <sub>8</sub> |

