

Application

Pole-top luminaire with asymmetric light distribution designed for the illumination of parking areas and roadways. Tool-less entry with hinged door for ease of maintenance. Provided with slip fitter to fit 3" O.D. poles.

Materials

- Clear safety glass
- Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy
- High temperature silicone gasket
- Mechanically captive stainless steel fasteners
- Silicone applied robotically to casting, plasma treated for increased adhesion
- Integral surge protector
- Pure anodized aluminum reflector

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 66

Weight: 19.0lbs.

EPA (Effective projection area): 0.8 sq. ft.

Electrical

- Operating voltage120-277VAC
- Minimum start temperature-40° C
- LED module wattage62.0W
- System wattage76.0W
- Controllability0-10V dimmable
- Color rendering indexRa > 80
- Luminaire lumens9454 lm
- LED service life (L70)60000hrs

LED color temperature

- 4000K (K4)
- 3500K (K35)
- 3000K (K3)
- 2700K (K27)


BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors

- Black (BLK)
- Silver (SLV)
- RAL:
- Bronze (BRZ)
- White (WHT)
- CUS:



Area/Roadway luminaire · Asymmetric · Single

	LED	A	B	C
B99523	62.0W	13 ³ / ₈	3	26

Type:

BEGA Product:

Project:

Modified:

Available options

- CUS Custom finish
- FSC Fusing
- IMS-L2 Integral motion sensor (48' x coverage at 8' AFG)
- IMS-L3 Integral motion sensor (40' x coverage at 20' AFG)
- IMS-L4 Integral motion sensor (60' x coverage at 40' AFG)
- IMS-L7 Integral motion sensor (100' x coverage at 40' AFG)
- MGU Marine grade undercoat
- RAL RAL finish

Available accessories

- BFSIR-100 Handheld configuration tool
- See individual accessory spec sheet for details.

