

Application

Pole-top luminaire with asymmetric light distribution designed for the illumination of parking areas and roadways. Tool-less entry with hinged door for ease of maintenance. Provided with slip fitter to fit 3" O.D. poles. DarkSky Approved (2700K and 3000K only).

Materials

- Clear safety glass
- Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy
- High temperature silicone gasket
- Mechanically captive stainless steel fasteners
- Silicone applied robotically to casting, plasma treated for increased adhesion
- Integral surge protector
- Pure anodized aluminum reflector

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 66

Weight: 24.9 lbs.

EPA (Effective projection area): 0.9 sq. ft.

Electrical

- Operating voltage120-277V AC
- Minimum start temperature-40° C
- LED module wattage94.2 W
- System wattage115.0 W
- Controllability0-10V dimmable
- Color rendering indexRa > 80
- Luminaire lumens12995 lm
- LED service life (L70)60000 hrs

LED color temperature

- 4000K (K4)
- 3500K (K35)
- 3000K (K3) (DarkSky Approved)
- 2700K (K27) (DarkSky Approved)


BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors

- Black (BLK)Bronze (BRZ)
- Silver (SLV)White (WHT)
- RAL:CUS:



Area/Roadway luminaire · Asymmetric · Single

	LED	A	B	C
B99527	94.2 W	13 ³ / ₈	3	32 ³ / ₈

Type:

BEGA Product:

Project:

Modified:

Available options

- 347V347V input
- CUSCustom finish
- FSCFusing
- IMS-L2Integral motion sensor (48' x coverage at 8' AFG)
- IMS-L3Integral motion sensor (40' x coverage at 20' AFG)
- IMS-L4Integral motion sensor (60' x coverage at 40' AFG)
- IMS-L7Integral motion sensor (100' x coverage at 40' AFG)
- MGUMarine grade undercoat
- RALRAL finish

Available accessories

- BFSIR-100Handheld configuration tool

See individual accessory spec sheet for details.

