Application

BEGA system bollard luminaire tube without components. BEGA system bollard tubes are designed for easy attachment to system bollard heads using an interlocking mechanism. An accompanying bollard head must be selected for proper installation.

Materials

Extruded aluminum

Marine grade, copper free (\leq 0.3% copper content) A360.0 aluminum alloy Die-cast aluminum

Interlocking stainless steel mounting mechanism for attachment of head and tube

Self-expanding sleeve anchors for pre-cast concrete

 $\ensuremath{\mathsf{NRTL}}$ listed to North American Standards, suitable for wet locations Protection class IP 65

Weight: 7.7 lbs.

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors

Black (BLK) Silver (SLV) Natural Bronze (NTB) Bronze (BRZ) White (WHT) RAL:

CUS:

Type:

BEGA Product:

Project: Modified:

Available options

CUS Custom finish

MGU Marine grade undercoat NTB Natural bronze (premium finish)

RAL RAL finish





 System bollard tube ⋅ No access door

 A
 B

 B99620
 5½
 26

System bollard summary · Round

The overview provides a compact summary of the possibilities for combining the various bollard heads with the bollard tubes and their additional functions.

For each bollard head you can find matching bollard tubes with and without components.

	System bollard heads with compatible tubes		Į								Y								
	BEGA bollard tubes Ø in inches	ø5½	ø7½	ø5½	ø7½	ø10¾	ø5½	ø7½	ø5½	ø7½	ø7½	ø7½	ø10¾	ø7½	ø10¾	ø7½	ø5½ (ø7½	ø10¾
	Without components in two heights	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
3	With integral floodlight		•		•			•		•	•	•		•		•		•	
•	With integral PIR motion sensor		•		•	•		•		•	•	•	•	•	•	•		•	•
	With emergency lighting battery		•		•	•		•		•	•	•	•	•	•	•		•	•
H	With drive-through protection					•							•		•				•
	With integral GFCI outlet		•		•	•		•		•	•	•	•	•	•	•		•	•
6	With integral 240V receptaclefor electric vehicles					•							•		•				•
	Wood bollard tubes	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•

Compatible heads · Ø5 1/2

B99853

6.0 W

System	bollard head · Unshielde	ed · 360°		System	bollard head · Shielded	with reflector · 360°			
B99719	LED 6.0W	A 5 ¹ / ₂	B 51/ ₂	B99852	LED 6.0W	A 5 ¹ / ₂	B 51/ ₂		
System	bollard head · Unshielde	ed with safety guard · 180	0	System bollard head \cdot Unshielded with safety guard \cdot 360°					
B99770	LED 6.0W	A 51/ ₂	B 51/ ₂	B84682	LED 6.0W	A 51/ ₂	В 7		
System	bollard head · Unshielde	ed with safety guard · 360	0	System bollard head · Non-illuminated cap					
B99760	LED 6.0W	A 51/2	B 517 ₂	B71126		A 51/ ₂	B 0 ³ / ₄		
System	bollard head · Shielded v	with reflector · 180°							