Application

BEGA system bollard luminaire tube with GFCI or USB convenience outlets behind a lockable access door. BEGA system bollard tubes are designed for easy attachment to system bollard heads using an interlocking mechanism. An accompanying bollard head must be selected for proper installation.

Materials

Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy Die-cast aluminum

Extruded aluminum

Mechanically captive stainless steel fasteners

Interlocking stainless steel mounting mechanism for attachment of head and tube

Pre-wired with 5-pole plug-in connectors for ease of installation Galvanized steel anchorage

NRTL listed to North American Standards, suitable for wet locations Protection class IP 65

Weight: 18.7 lbs.

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors

Black (BLK) Silver (SLV) Natural Bronze (NTB) CUS:

Bronze (BRZ) White (WHT) RAL:

Type:

BEGA Product:

Project: Modified:

Available options

70896 Direct burial anchorage (replaces included

anchorage kit, pre-shippable)

CUS Custom finish

MAG Magnetic door closure MGU Marine grade undercoat Natural bronze (premium finish) NTB RAL

RAL finish

USB1 1 GFCI & 1 USB receptacle

USB2 2 USB receptacles

Included (available for pre-shipment)

B79818 Anchorage kit





System bollard tube · Integral GFCI outlet

	А	В	
B99626	71/2	32	

System bollard summary · Round

The overview provides a compact summary of the possibilities for combining the various bollard heads with the bollard tubes and their additional functions.

For each bollard head you can find matching bollard tubes with and without components.

	System bollard heads with compatible tubes										T		3	72.00	B	7	7	ĺ		
	BEGA bollard tubes Ø in inches	ø5½	ø7½	ø5½	ø7½	ø10¾	ø5½	ø7½	ø5½	ø7½	ø7½	ø7½	ø10¾	ø7½	ø10¾	ø7½		ø5½	ø7½	ø10¾
	Without components in two heights	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		•	•	•
3	With integral floodlight		•		•			•		•	•	•		•		•			•	
•	With integral PIR motion sensor		•		•	•		•		•	•	•	•	•	•	•			•	•
	With emergency lighting battery		•		•	•		•		•	•	•	•	•	•	•			•	•
I	With drive-through protection					•							•		•					•
	With integral GFCI outlet		•		•	•		•		•	•	•	•	•	•	•			•	•
8	With integral 240V receptaclefor electric vehicles					•							•		•					•
	Wood bollard tubes	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		•	•	•

Compatible tubes · Ø7 1/2

System bollard tube · No access door							
		Α	В				
B99615		71/2	141/2				
System bollard tube · No access door							
		A	В				
B96177		71/2	32				
System bollard tube · With access door							
		А	В				
B99622		71/2	32				
System bollard tube · Integral floodlight							
	LED	A	В				
B99644	19.3W	71/2	32				

System bollard tube · Integral emergency lighting battery						
	А	В				
B99635	A 7 ¹ / ₂	32				
System bollard tube · Integral GFCI outlet						
	А	В				
B99626	A 7 ¹ / ₂	32				
Wood system bollard tube · Round						
	А	В				
B84464	7 ¹ / ₂	321/8				
System bollard tube · Integral PIR motion sensor						
	А	В				
B99658	71/2	32				