

**BEGA LED system bollard - bollard tube for luminaire height 43 1/4 with integrated GFCI outlet**

**Post construction:** One piece extruded aluminum, 3/16" wall thickness with a one piece base, internally welded into an assembly. Provided with lockable access door. Die castings are marine grade, copper free ( $\leq 0.3\%$  copper content) A360.0 aluminum alloy. Designed to accept BEGA LED system bollard heads of 10 3/8" in diameter.

**Integrated components:** Bollard tube provided with integrated 20A duplex GFCI receptacle behind lockable door, safety lock with two (2) keys. GFI covers are intended for portable tools or other portable equipment connected to the outlet when attended. Wet location listed when cover is closed. Optionally available with USB receptacle.

**Anchor base:** Heavy cast aluminum, slotted for precise alignment. Mounts to BEGA 79 818 anchorage kit. Bollard secures to base with one stainless steel set screw. The mounting system allows the luminaire to be adjusted independent of anchor bolt orientation.

**Finish:** All BEGA standard finishes are polyester powder coat with minimum 3 mil thickness. Available in four standard BEGA colors: Black (BLK); White (WHT); Bronze (BRZ); Silver (SLV). To specify, add appropriate suffix to catalog number. Custom colors supplied on special order.

**Note:** See below for compatible LED system bollard heads. See specifications for details.

**CSA certified** to U.S. and Canadian standards, suitable for wet locations. Protection class IP65

**Weight:** 31.1 lbs.

Type:  
 BEGA Product:  
 Project:  
 Voltage:  
 Color:  
 Options:  
 Modified:



99 777

99 778

99 865



Optional  
 USB & GFCI

Optional  
 USB port

