Application

BEGA system bollard head with shielded 360° light distribution. Simply order the bollard head and also the required bollard tube in various heights and options. Both modules can be joined together easily and quickly during the installation.

Materials

Clear safety glass with white ceramic coating

Die-cast aluminum

Extruded aluminum

Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy High temperature silicone gasket

Mechanically captive stainless steel fasteners

Interlocking stainless steel mounting mechanism for attachment of head and tube

Stainless steel helicoils

Pure anodized aluminum reflector surface

NRTL listed to North American Standards, suitable for wet locations Protection class IP 65

Weight: 17.2lbs.

Electrical

120-277VAC Operating voltage Minimum start temperature -30° C LED module wattage 29.4 W System wattage 34.0 W

Controllability 0-10V dimming down to 1%

Color rendering index Ra > 80Luminaire lumens 1637 lm LED service life (L70) 60000 hrs

LED color temperature

4000K (K4) 3500K (K35) 3000K (K3) 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors

Black (BLK) Bronze (BRZ) White (WHT) Silver (SLV) Natural Bronze (NTB) RAL:

CUS:

Type:

BEGA Product:

Project: Modified:

Available options

CUS Custom finish MGU Marine grade undercoat NTB Natural bronze (premium finish) **RAL**

RAL finish





System bollard head · Shielded · 360°

В

LED B99865 10³/₈ 29.4 W

System bollard summary · Round

The overview provides a compact summary of the possibilities for combining the various bollard heads with the bollard tubes and their additional functions.

For each bollard head you can find matching bollard tubes with and without components.

	System bollard heads with compatible tubes		報からも							V			22.50					ı
	BEGA bollard tubes Ø in inches	ø5½ ø7!	/ ₂ ø5	07½	ø10¾	ø5½	ø7½	ø5½	ø7½	ø7½	ø7½	ø 10 ¾	ø7½	ø10¾	ø7½	ø5½	g 07½	ø10¾
	Without components in two heights	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
③	With integral floodlight	•		•			•		•	•	•		•		•		•	
•	With integral PIR motion sensor	•		•	•		•		•	•	•	•	•	•	•		•	•
	With emergency lighting battery	•		•	•		•		•	•	•	•	•	•	•		•	•
	With drive-through protection				•							•		•				•
	With integral GFCI outlet	•		•	•		•		•	•	•	•	•	•	•		•	•
<u> </u>	With integral 240V receptaclefor electric vehicles				•							•		•				•
	Wood bollard tubes	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•

Compatible tubes · Ø10 3/8

System bollard tube · No access	s door						
	A	В					
B99619	103/8	143/4					
System bollard tube · With access door							
	А	В					
B99624	103/8	341/2					
System bollard tube · Integral PIR motion sensor							
	Α	В					
B99659	A 10 ³ / ₈	341/2					
System bollard tube · Integral emergency lighting battery							
	Α	В					
B99636	103/8	341/2					

System bollard tube · Drive-through protection							
	Α	В					
B84623	103/8	343/8					
System bollard tube · Ir	ntegral GFCI outlet						
	А	В					
B99627	103/8	341/2					
System bollard tube · Integral 240V receptacle							
	Α	В					
B98010	103/8	39					
Wood system bollard tube · Round							
	А	В					
B84465	10³/ ₈	341/2					