

Application

Pole-top luminaire with asymmetric light distribution. These luminaires provide light in front of the luminaire to uniformly wash surfaces for plazas and parking lots.

Materials

- Clear safety glass
- Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy
- High temperature silicone gasket
- Mechanically captive stainless steel fasteners
- Galvanized steel anchorage
- Pure anodized aluminum reflector

NRTL listed to North American Standards, suitable for wet locations  
Protection class IP 65

Weight: 34.3lbs.

EPA (Effective projection area): 0.8 sq. ft.

Electrical

- Operating voltage120-277VAC
- Minimum start temperature-30° C
- LED module wattage15.6W
- System wattage18.0W
- Controllability0-10V dimming down to 1%
- Color rendering indexRa > 80
- Luminaire lumens2026 lm
- LED service life (L70)60000hrs

LED color temperature

- 4000K (K4)
- 3500K (K35)
- 3000K (K3)
- 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors

- Black (BLK)
- Silver (SLV)
- RAL:
- Bronze (BRZ)
- White (WHT)
- CUS:

Type:

BEGA Product:

Project:

Modified:

Available options

- CUSCustom finish
- IMS-L2Integral motion sensor (48' □ coverage at 8' AFG)
- IMS-L3Integral motion sensor (40' □ coverage at 20' AFG)
- IMS-L4Integral motion sensor (60' □ coverage at 40' AFG)
- IMS-L7Integral motion sensor (100' □ coverage at 40' AFG)
- MGUMarine grade undercoat
- RALRAL Classic, matte finish

Available accessories

- BFSIR-100Handheld configuration tool

See individual accessory spec sheet for details.

Included (available for pre-shipment)

- 722-XXXPole assembly



Adjustable luminaire with pole · Asymmetric · Single

	LED	A	B	C
B99868	15.6W	10 <sup>1</sup> / <sub>4</sub>	98 <sup>1</sup> / <sub>2</sub>	12 <sup>1</sup> / <sub>2</sub>