


# BEGA

File: Modular Furniture\_Recessed Horizontal\_IES.ies

TEST: BE\_24216K4  
 TEST LAB: BEGA  
 DATE: 02/01/2017  
 LUMINAIRE: 24 216K4  
 LAMP: (2X) 11.5W LED

\*As seen in open benches within the BEGA Modular Furniture System (i.e. M027)



## Characteristics



IES Classification	Type VS
Longitudinal Classification	Very Short
Lumens Per Lamp	N.A. (absolute)
Total Lamp Lumens	N.A. (absolute)
Luminaire Lumens	2516
Downward Total Efficiency	N.A.
Total Luminaire Efficiency	N.A.
Luminaire Efficacy Rating (LER)	180
Total Luminaire Watts	28
Ballast Factor	1.00
Upward Waste Light Ratio	0.00
Max. Cd.	866.4 (95H, 2.5V)
Max. Cd. (<90 Vert.)	866.4 (95H, 2.5V)
Max. Cd. (At 90 Deg. Vert.)	.6 (0.0%Lum)
Max. Cd. (80 to <90 Deg. Vert.)	92.8 (3.7%Lum)
Cutoff Classification (deprecated)	N.A. (absolute)

## Lum. Classification System (LCS)

LCS Zone	Lumens	%Lamp	%Lum
FL (0-30)	338.3	N.A.	13.4
FM (30-60)	653.8	N.A.	26.0
FH (60-80)	246.4	N.A.	9.8
FVH (80-90)	19.8	N.A.	0.8
BL (0-30)	338.1	N.A.	13.4
BM (30-60)	653.7	N.A.	26.0
BH (60-80)	246.3	N.A.	9.8
BVH (80-90)	19.8	N.A.	0.8
UL (90-100)	.1	N.A.	0.0
UH (100-180)	< 0.05	N.A.	0.0
Total	2516.5	N.A.	100.0

## BUG Rating B1-U0\*-G0

Fixture has measured rating of U1 due to testing above 90 degrees and stray light from reflection off of the fixture body. Upon visual inspection of luminaire, there is no significant uplight (<.5%), and it has therefore been assigned a value of U0. Consult factory for more information.



Mounting Height: 1.2 ft.  
 (Bottom of bench seat)

Grid Spacing: 1.5 ft.

In the interest of product improvement, BEGA reserves the right to make technical changes without notice.