


Hardware Included:

- M10 x 80mm Anchors
- Washer
- Cap nut

Overview:

Weight: 33.1 lbs.



Dimensions

- A:** 12-5/8"
B: 2-3/4"
C: 35-3/8"
D: 5-1/2"



Notice to Installer:

1. Ensure that the installation site is level, stable, and free from any obstructions.
2. Verify that the ground is suitable for anchoring the bike rack securely.
3. Gather all the necessary tools and equipment required for the installation, such as a shovel, level, screwdriver, hammer, and drill (if applicable).
NOTE: An epoxy such as Loctite PC 9410 or equivalent is required for anchor installation. Epoxy must be provided by installing contractor and chosen to best suit installation application.
4. Check for underground utilities or cables before digging or anchoring the bike rack.
5. Threaded rods provided to be epoxied into place.
6. Ensure that the anchoring or mounting method is suitable for the type of surface and provides adequate stability and security.
7. Consider any local regulations or codes regarding outdoor furniture installation and safety requirements.

Install Instructions:

1. Choose a suitable location for the outdoor bike rack. Ensure it is on a level surface that provides stability and comfort.
2. Clear the installation area of any debris, rocks, or other obstacles.
3. Establish bike rack location and mark anchor locations for drilling.
NOTE: When installing in soft scape (i.e. mulch, gravel) ensure a suitable concrete pad/foundation is provided to properly anchor bike rack
4. Install threaded anchors (provided) at the marked locations, and epoxy anchors into place. (Please allow ample time for epoxy to cure)
NOTE: An epoxy such as Loctite PC 9410 or equivalent is required for anchor installation. Epoxy must be provided by installing contractor and chosen to best suit installation application.
5. Install bike rack over installed threaded anchors, and bolt to the foundation.
6. Ensure all components are securely fastened.

Maintenance & Care:

Should cleaning be required, use a rag/ cloth dampened with water to remove any contaminates/particulates from the surface of the material. The removal of greasy, oily or sooty substances can take place with the use of white spirit free of aromatic compounds or isopropyl alcohol. Mild cleaning solutions can be utilized though are not required if maintenance is needed.